



## SUN Series (Grow Light) Specifications

Model	Light Source	Power (W)	Luminous Flux(LM)	Working Voltage(V/Hz)	Wave Range	Light Attenuation	Dimensions (mm)
MG-3030-56	56x1W	60	1000	80-220V/47-63Hz	R:640-690 B:420-470	5% (1000h)	300x300x30
MG-3030-88	88x1W	90	1500				
MG-3060-112	112x1W	120	1900				600x300x30
MG-3060-176	176x1W	190	3000				
MG-3090-168	168x1W	180	2900				900x300x30
MG-3090-264	264x1W	285	4500				
MG-30120-224	224x1W	250	3800				1200x300x30
MG-30120-352	352x1W	380	6000				

## SUN Series (Grow Light) Specifications

Model	Light Source	Power (W)	Luminous Flux(LM)	Working Voltage(V/Hz)	Wave Range	Light Attenuation	Dimensions (mm)
MG-1530-28	28x1W	30	500	80-220V/47-63Hz	R:640-690 B:420-470	5% (1000h)	300x150x30
MG-1530-44	44x1W	46	800				
MG-1560-56	56x1W	60	1000				600x150x30
MG-1560-88	88x1W	90	1500				
MG-1590-84	84x1W	88	1500				900x150x30
MG-1590-132	132x1W	145	2300				
MG-15120-112	112x1W	120	1900				1200x150x30
MG-15120-176	176x1W	190	3000				

## Illumination Picture

